



FIRE & SECURITY

MARLOWE Critical Services

**t.** 020 8974 1177  
**e.** [connect@fafs.biz](mailto:connect@fafs.biz)  
**w.** [www.fafs.biz](http://www.fafs.biz)



Compliance. Assured.





# Contents

2	Commander Fire Extinguishers
12	CommanderEDGE Fire Extinguishers
24	Contempo Fire Extinguishers
32	Trolleys and Covers
34	Stands
36	Cabinets
37	Signs
40	Alarms
41	Fire Protection Products



... safety pin



Free hose  
Aim nozzle  
at base of fire



Squeeze handles



Tested to BS EN3-7. Safe for inadvertent use on live electrical fires up to 1000V  
CAUTION:  
Depressurise and recharge after any use.  
Check weight at least once a year.  
Protect from frost.

# COMMANDER®

CheckFire Ltd, Caerphilly, CF83 3HU



BS EN3-7  
KM 5030



RECHARGE AFTER USE  
THIS EXTINGUISHER SHOULD  
SERVICED AT LEAST ONCE  
A QUALIFIED COMPETENT PERSON  
ACCORDANCE WITH BS EN 3-7  
RECHARGING SHOULD BE DONE  
OUT TO BS 6643 PART 1  
COMPONENTS RECOMMENDED BY  
THE MANUFACTURER

MODEL WSWX6 (W6R)  
EXTINGUISHER MEDIUM  
OPERATING TEMPERATURE RANGE  
TEST PRESSURE 27 BAR  
PRESSURISING GAS NITROGEN





With one of the widest ranges available on the market today, Commander is firmly regarded as a true market leader.

Time has proved these portable fire extinguishers as a dependable choice for almost any situation and reliable performance is guaranteed. What's more, the 6ltr/kg and 9ltr/kg units now carry the BSI Kitemark certification.

# Commander Water Fire Extinguishers

A water-based fire extinguisher is a popular choice for Class A fires (combustible materials). Water fire extinguishers work by cooling the fuel and ensuring it burns at a much slower pace until the fire is extinguished.

Most premises are required to have a water or foam extinguisher - they're often found in busy places like offices, schools and hospitals. With a low-cost price and ease of maintenance, it's easy to see why water fire extinguishers are a preferred choice for many businesses. The Commander range of water fire extinguishers benefits from the following:

## Features

- Kitemarked\* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty\*\*
- MED approval on selected products



### 3ltr Water Compact PLUS

CODE	WSEX3A
CAPACITY	3 LITRE
FIRE RATING	13A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN

### 6ltr Water PLUS Spray

CODE	WSWX6
CAPACITY	6 LITRE
FIRE RATING	21A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN



### 9ltr Water PLUS Spray

CODE	WSWX9
CAPACITY	9 LITRE
FIRE RATING	27A
EXTINGUISHER MEDIUM	WATER + ADDITIVE
WORKING PRESSURE	14 BAR
TEMPERATURE RANGE	+5-+60°C
CYLINDER MATERIAL	STEEL
PRESSURING GAS	NITROGEN







# Commander Foam Fire Extinguishers

Most commonly used on Class B fires (flammable liquids), a foam fire extinguisher is also a recommended choice for Class A risk areas (those featuring combustible materials). These extinguishers perform a cooling function and quickly smother burning materials, while the foam agent helps prevent the fire reigniting.

Foam fire extinguishers shouldn't be used on kitchen fires or those with an electrical source. However, they're ideal for office environments, hospitals, schools and other spaces where organic materials play a large role in the landscape. The Commander range of foam fire extinguishers benefits from the following:

## Features

- Kitemarked\* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty\*\*
- MED approval on selected products



**1ltr  
AFF Foam**

CODE FSEX1
CAPACITY 1 LITRE
FIRE RATING 5A 21B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**3ltr  
AFF Foam**

CODE FSEX3
CAPACITY 3 LITRE
FIRE RATING 13A 55B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 12 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**6ltr  
AFF Foam**

CODE FSWX6
CAPACITY 6 LITRE
FIRE RATING 21A 144B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9ltr  
AFF Foam**

CODE FSWX9
CAPACITY 9 LITRE
FIRE RATING 27A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN







**AFF Foam**

- Use for use on Class A, B and C fires
- Use for use on Class A, B and C fires
- Do NOT use on electrical fires
- Do NOT use on flammable liquids

**Water**

- Use for use on Class A fires
- Do NOT use on Class B and C fires
- Do NOT use on electrical fires
- Do NOT use on flammable liquids

**Foam**

**FIRE EXTINGUISHER**  
6 Litre FOAM SPRAY  
21A 144B

For use on burning liquid free Class A and B fires, wood, paper, textile and grease fires. Class A and B.

- Use upright
- Pull out safety pin
- Free hose
- Aim nozzle at base of fire
- Squeeze handles

**COMMANDER**

**Water**

PLUS

**FIRE EXTINGUISHER**  
6 Litre WATER SPRAY PLUS  
21A

For use on wood, paper, textile and grease fires. Class A and B.

- Use upright
- Pull out safety pin
- Free hose
- Aim nozzle at base of fire
- Squeeze handles

**COMMANDER**

# Commander Powder Fire Extinguishers

A dry powder fire extinguisher is extremely versatile. It's suitable for use on Class A (combustible materials), Class B (flammable liquids) and Class C (flammable gases) fires. It's for this reason they're known as 'ABC' extinguishers. This extinguisher smothers fires by producing a thick barrier between the fuel and the source of oxygen.

A powder fire extinguisher shouldn't be used in confined spaces because the powder can easily be inhaled and it leaves a residue that can be difficult to clean up. Consider this extinguisher for premises including garage forecourts, commercial boiler rooms and workspaces that feature welding. The Commander range of powder fire extinguishers benefits from the following:

## Features

- Kitemarked\* and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty\*\*
- MED approval on selected products



**3kg ABC  
Dry Powder**

CODE DPEX3
CAPACITY 3KG
FIRE RATING 13A 89B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN

**6kg ABC  
Dry Powder**

CODE DPWX6
CAPACITY 6KG
FIRE RATING 43A 223B C
EXTINGUISHER MEDIUM ABC 30
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9kg ABC  
Dry Powder**

CODE DPWX9
CAPACITY 9KG
FIRE RATING 55A 233B C
EXTINGUISHER MEDIUM ABC 30
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN









# Commander Wet Chemical Fire Extinguishers

A wet chemical fire extinguisher is specifically designed for use on Class F fires (cooking oils and fats), making it the ideal solution for the demands of commercial kitchen and canteen environments.

This type of extinguisher works by creating a layer of foam on the burning oil or fat, stopping the supply of oxygen so the fire isn't fuelled any further. Available in a choice of sizes, find the ideal wet chemical fire extinguisher for your requirements. The Commander range of wet chemical fire extinguishers benefits from the following:

## Features

- Manufactured to BS EN3
- Corrosion-resistant cylinders
- Polyethylene internal lining
- Full range of spare parts available
- Easy-clean design



### 3ltr Wet Chemical

CODE  
WCEX3

CAPACITY  
3 LITRE

FIRE RATING  
8A 75F

EXTINGUISHER MEDIUM  
WET CHEMICAL

WORKING PRESSURE  
7 BAR

TEMPERATURE RANGE  
+5-+60°C

CYLINDER MATERIAL  
STAINLESS STEEL

PRESSURING GAS  
NITROGEN

### 6ltr Wet Chemical

CODE  
WCEX6

CAPACITY  
6 LITRE

FIRE RATING  
13A 75F

EXTINGUISHER MEDIUM  
WET CHEMICAL

WORKING PRESSURE  
7 BAR

TEMPERATURE RANGE  
+5-+60°C

CYLINDER MATERIAL  
STAINLESS STEEL

PRESSURING GAS  
NITROGEN



1  
All food must be covered and dated



**COMMANDER**



**Free hose  
Aim nozzle  
at base of fire**



**Squeeze handles**



**WARNING:**  
Do not use on liquid fires or live electrical equipment  
Depressurise and recharge after any use  
Check weight at least once a year  
Protect from frost

For use on wood, paper, textile and similar  
Class A fires.

**COMMANDER EDGE**

CHECKFIRE, Pontywindy Industrial Estate, Caerphilly, UK, CF83 3HU



RECHARGE AFTER USE  
THIS EXTINGUISHER SHOULD  
SERVICED AT LEAST ONCE  
A QUALIFIED COMPETENT PERSON  
ACCORDANCE WITH BS 6843 PART 1  
RECHARGING SHOULD BE DONE  
OUT TO BS 6843 PART 1  
COMPONENTS RECOMMENDED BY  
THE MANUFACTURER

MODEL WS 5E (10)  
EXTINGUISHER MEDIUM WATER  
OPERATING TEMPERATURE RANGE  
TEST PRESSURE: 30 BAR (435 PSI)  
PRESSURISING GAS: NITROGEN



With one of the widest ranges available on the market today, CommanderEDGE is firmly established as the market leader.

The range is fully Kitemarked by BSI and is the choice of the professional with its reassuring mixture of performance, quality and value.



# CommanderEDGE Water Fire Extinguishers

Ideal for Class A fire risk areas (those featuring combustible materials), water-based extinguishers remain a popular choice for many businesses. Pointed at the base of the fire, this extinguisher releases water to cool the fuel, ensuring it burns at a slow pace until it's completely extinguished.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. Available in six-litre and nine-litre units, CommanderEDGE water fire extinguishers come with a five-year warranty. What's more, the 6ltr Water Compact 34, with additive, boasts a remarkable 34A fire rating, making it an exceptional powerhouse for its light weight. The CommanderEDGE range of water fire extinguishers benefits from great design, a strong plastic base skirt and the following:

## Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty\*
- MED approval on selected products



**6ltr  
Water**

CODE WS6E
CAPACITY 6 LITRE
FIRE RATING 13A
EXTINGUISHER MEDIUM WATER
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5-+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**6ltr Water  
Compact 34**

CODE WS6EA
CAPACITY 6 LITRE
FIRE RATING 34A
EXTINGUISHER MEDIUM WATER
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5-+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9ltr  
Water**

CODE WS9E
CAPACITY 9 LITRE
FIRE RATING 13A
EXTINGUISHER MEDIUM WATER
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5-+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN





<b>Water</b>		DO NOT use on electrical equipment	DO NOT use on flammable liquids	DO NOT use on flammable gases	DO NOT use on cooking oil	DO NOT use on grease	DO NOT use on paint	DO NOT use on varnish	DO NOT use on wax	DO NOT use on other materials

**Water**

**FIRE EXTINGUISHER**  
6 LITRE WATER  
12 A

- Use upright  
Pull out safety pin
- Free hose  
Aim nozzle  
at base of fire
- Squeeze handles

**CAUTION:** Do not use on liquid fires. Only water and therefore only use on fires which do not involve a gas or other flammable liquid.

For use on wood, paper, fabric and similar. **DO NOT USE for electrical use or electrical fires.**

**COMMANDER EDGE**

100000, (Incorporating Industrial Estate, County, W, 0745 000)



# CommanderEDGE Foam Fire Extinguishers

This type of extinguisher is an ideal choice for Class A and B risk areas (those featuring combustible materials and flammable liquids). A foam extinguisher performs a cooling function, while a layer of foam floats on top of the burning liquid to prevent reignition.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. Available in two-litre, six-litre and nine-litre units, CommanderEDGE foam extinguishers are a robust and reliable solution for tackling Class A and B fires. Plus, for the environmentally conscious, EnviroFoam's low fluorine content ensures it's less harmful to the environment than regular foams. The CommanderEDGE range of foam fire extinguishers benefits from great design and the following:

## Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty\*
- MED approval on selected products



**2ltr  
AFF Foam**

CODE FS2E
CAPACITY 2 LITRE
FIRE RATING 8A 55B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**6ltr  
AFF Foam**

CODE FS6E
CAPACITY 6 LITRE
FIRE RATING 13A 144B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**6ltr  
EnviroFoam**

CODE FS6ECO
CAPACITY 6 LITRE
FIRE RATING 27A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**9ltr  
AFF Foam**

CODE FS9E
CAPACITY 9 LITRE
FIRE RATING 21A 183B
EXTINGUISHER MEDIUM AFF FOAM
WORKING PRESSURE 14 BAR
TEMPERATURE RANGE +5+60°C
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN





**EniroFoam**

# Foam

## FIRE EXTINGUISHER

6 Litre FOAM SPRAY  
27A 183B

For use on burning liquid fires (Class B) and wood, paper, textile and similar Class A fires



Use upright  
Pull out safety pin



Free hose  
Aim nozzle  
At base of fire



Squeeze handles



**CAUTION:**

Tested to BS EN3-7 safe for inadvertent use on electrical fires.  
Depressurise and recharge after any use.  
Check weight at least once a year. Protect from frost

**COMMANDER EDGE**

CheckFire, Caerphilly, CF83 3HU

# CommanderEDGE Powder Fire Extinguishers

A dry powder fire extinguisher is extremely versatile, suitable for use on Class A (combustible materials), Class B (flammable liquids) and Class C (flammable gases) fires. It's for this reason they're known as 'ABC' extinguishers.

This extinguisher smothers fires by producing a thick barrier between the fuel and the source of oxygen. A powder fire extinguisher shouldn't be used in confined spaces because the powder can easily be inhaled and it leaves a residue that can be difficult to clean up. Consider this extinguisher for premises including garage forecourts, commercial boiler rooms and workspaces that feature welding. This range benefits from the following:

## Features


- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty\*
- MED approval on selected products




**1kg ABC  
Dry Powder**

CODE DP1E
CAPACITY 1KG
FIRE RATING 8A 34B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN



**2kg ABC  
Dry Powder**

CODE DP2E
CAPACITY 2KG
FIRE RATING 13A 70B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN
 



**4kg ABC  
Dry Powder**

CODE DP4E
CAPACITY 4KG
FIRE RATING 21A 89B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN


**6kg ABC  
Dry Powder**

CODE DP6E
CAPACITY 6KG
FIRE RATING 34A 233B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN
 

**9kg ABC  
Dry Powder**

CODE DP9E
CAPACITY 9KG
FIRE RATING 55A 233B C
EXTINGUISHER MEDIUM ABC 40
WORKING PRESSURE 14 BAR
CYLINDER MATERIAL STEEL
PRESSURING GAS NITROGEN
 







# CommanderEDGE MultiCHEM Fire Extinguishers

For an innovative fire-fighting solution, choose the latest in high-performance multi-class extinguishers.

MultiCHEM is an ABF-rated extinguisher ideal for flammable liquid fires involving large quantities of fuel and a big surface area. But it's also suitable for deep fat fryer fires too.

The extinguisher's 34A rating – the industry's highest for a six-litre extinguisher – means that it's capable of tackling a sizeable fire. This ground-breaking extinguisher is also available in two and three litre sizes, as well as unique, aesthetically pleasing finishes, to perfectly tailor to your needs. This range benefits from the following:

## Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available
- Five-year warranty\*
- MED approval on selected products



### 2ltr MultiCHEM

CODE  
FS2EMC

CAPACITY  
2 LITRE

FIRE RATING  
8A 70B 25F

EXTINGUISHER MEDIUM  
FOAM

WORKING PRESSURE  
12 BAR

TEMPERATURE RANGE  
-5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN



### 3ltr MultiCHEM

CODE  
FS3EMC

CAPACITY  
3 LITRE

FIRE RATING  
13A 89B 40F

EXTINGUISHER MEDIUM  
FOAM

WORKING PRESSURE  
12 BAR

TEMPERATURE RANGE  
-5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN



### 6ltr MultiCHEM

CODE  
FS6EMC

CAPACITY  
6 LITRE

FIRE RATING  
34A 233B 75F

EXTINGUISHER MEDIUM  
FOAM

WORKING PRESSURE  
12 BAR

TEMPERATURE RANGE  
-5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN







# CommanderEDGE CO2 Fire Extinguishers

A carbon dioxide (CO2) extinguisher is the perfect choice for Class B fires (those involving flammable liquids). However, it's also suitable for use on electrical fires because it won't damage electrical equipment or machinery. Carbon dioxide suffocates a fire and displaces oxygen in the air.

CommanderEDGE extinguishers prioritise high performance, superb quality and unrivalled value. These CO2 extinguishers are among the finest on the market. Aluminium or alloy squat bodies (in the 2kg models) allow for ease of handling, while in the 5kg models, you can rely on a best-in-class 89B fire rating. The CommanderEDGE range of CO2 fire extinguishers benefits from the following:

## Features

- Kitemarked and Manufactured to BS EN3
- Super strong base skirt for protection
- Corrosion-resistant finish
- Polyethylene internal lining
- Distinctive black horn
- Full range of spare parts available
- Five-year warranty\*
- MED approval on selected products

			
<b>2kg CO2</b>	<b>5kg CO2</b>	<b>2kg CO2 Aluminium</b>	<b>5kg CO2 Aluminium</b>
CODE CO2E	CODE CO2E	CODE CO2EA	CODE CO2EA
CAPACITY 2KG	CAPACITY 5KG	CAPACITY 2KG	CAPACITY 5KG
FIRE RATING 34B	FIRE RATING 70B	FIRE RATING 34B	FIRE RATING 89B
EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2	EXTINGUISHER MEDIUM CO2
WORKING PRESSURE 56 BAR @ 20°C	WORKING PRESSURE 56 BAR @ 20°C	WORKING PRESSURE 56 BAR @ 20°C	WORKING PRESSURE 56 BAR @ 20°C
TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C	TEMPERATURE RANGE -20+60°C
CYLINDER MATERIAL ALLOY STEEL	CYLINDER MATERIAL ALLOY STEEL	CYLINDER MATERIAL ALUMINIUM	CYLINDER MATERIAL ALUMINIUM
 	 	 	 





CO2

- Safe for use on: Electrical fires
- Safe for use on: Flammable liquids
- Safe for use on: Flammable gases
- Safe for use on: Soluble solids
- Safe for use on: Class B fires
- Safe for use on: Class C fires
- Safe for use on: Class D fires
- Safe for use on: Class E fires
- Safe for use on: Class F fires
- Safe for use on: Class K fires
- Safe for use on: Class L fires
- Safe for use on: Class M fires
- Safe for use on: Class N fires
- Safe for use on: Class O fires
- Safe for use on: Class P fires
- Safe for use on: Class Q fires
- Safe for use on: Class R fires
- Safe for use on: Class S fires
- Safe for use on: Class T fires
- Safe for use on: Class U fires
- Safe for use on: Class V fires
- Safe for use on: Class W fires
- Safe for use on: Class X fires
- Safe for use on: Class Y fires
- Safe for use on: Class Z fires

CO<sub>2</sub>

FIRE EXTINGUISHER  
2kg CARBON DIOXIDE

- Use upright
- Pull out safety pin
- Lift horn and aim at base of fire
- Squeeze handles

B 4

COMMANDER EDGE

DAKEN

COMMANDER EDGE





Use upright.  
Pull out safety pin.



Free hose.  
Aim nozzle at base of fire.



Squeeze handles.



**CAUTION:**

Do not use on live electrical equipment.  
Despressurise and recharge after every use.  
Check weight at least once a year.  
Protect from frost.

CONTEMPO





A fire extinguisher is a vital piece of equipment and, for any space that particularly prides itself on its aesthetic, the Contempo range – an industry first – has arrived.

The very finest interior finishes are beautifully researched and designed. Contempo provides stunning hand-finished extinguishers to complement the most exquisite interior – and nine-litre models can be available on request.

# Contempo Polished Gold

Synonymous with luxury, these hand-finished polished gold extinguishers serve as a stunning addition to elegant interiors.

Whether you are fitting out a stately home, palace or a castle, these extinguishers are a perfect solution. These are electro plated to give a stunning mirror finish. And with the matching polished gold tubular stands and ID signs, this range truly is elegance in fire defence. The Contempo range of Polished Gold fire extinguishers benefits from the following:

## Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty\*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)
- 9ltr models available. More information on request.



**2kg CO2  
Polished Gold**

CODE  
COEX2PG

CAPACITY  
2KG

FIRE RATING  
34B

EXTINGUISHER MEDIUM  
CO2

WORKING PRESSURE  
56 BAR @ 20°C

TEMPERATURE RANGE  
-20+60°C

CYLINDER MATERIAL  
ALLOY STEEL

**6ltr AFF Foam  
Polished Gold**

CODE  
FSEX6PG

CAPACITY  
6 LITRES

FIRE RATING  
13A 144B

EXTINGUISHER MEDIUM  
AFF FOAM

WORKING PRESSURE  
14 BAR

TEMPERATURE RANGE  
+5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN

**6ltr MultiCHEM  
Polished Gold**

CODE  
FSEX6MCPG

CAPACITY  
6 LITRES

FIRE RATING  
34A 233B 75F

EXTINGUISHER MEDIUM  
FOAM

WORKING PRESSURE  
12 BAR

TEMPERATURE RANGE  
-5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN

**6ltr Water  
Polished Gold**

CODE  
WSEX6PG

CAPACITY  
6 LITRES

FIRE RATING  
13A

EXTINGUISHER MEDIUM  
WATER

WORKING PRESSURE  
14 BAR

TEMPERATURE RANGE  
+5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN

**6kg Powder  
Polished Gold**

CODE  
DPEX6PG

CAPACITY  
6KG

FIRE RATING  
34A 233B C

EXTINGUISHER MEDIUM  
ABC 40

WORKING PRESSURE  
14 BAR

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN







# Contempo Antique Copper

Truly an industry-first, these exquisite extinguishers have been hand-finished. Each one is unique in its beauty.

Perfect for modern bars and restaurants, luxury hotels and contemporary commercial interiors, this is fire safety equipment that deserves to be on show. And with the matching brushed Antique Copper tubular stands and ID signs, this range exudes elegance as well as providing all the practical features and meeting industry standards. This unique range benefits from the following:

## Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty\*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)



**2kg CO2 Brushed  
Antique Copper**

CODE  
COEX2AC

CAPACITY  
2KG

FIRE RATING  
34B

EXTINGUISHER MEDIUM  
CO2

WORKING PRESSURE  
56 BAR @ 20 C

TEMPERATURE RANGE  
-20+60°C

CYLINDER MATERIAL  
ALLOY STEEL

**6ltr AFF Foam  
Antique Copper**

CODE  
FSEX6AC

CAPACITY  
6 LITRES

FIRE RATING  
13A 144B

EXTINGUISHER MEDIUM  
AFF FOAM

WORKING PRESSURE  
14 BAR

TEMPERATURE RANGE  
+5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN

**6ltr MultiCHEM  
Antique Copper**

CODE  
FSEX6MCAC

CAPACITY  
6 LITRES

FIRE RATING  
34A 233B 75F

EXTINGUISHER MEDIUM  
FOAM

WORKING PRESSURE  
12 BAR

TEMPERATURE RANGE  
-5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN

**6ltr Water  
Antique Copper**

CODE  
WSEX6AC

CAPACITY  
6 LITRES

FIRE RATING  
13A

EXTINGUISHER MEDIUM  
WATER

WORKING PRESSURE  
14 BAR

TEMPERATURE RANGE  
+5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN

**6kg Powder  
Antique Copper**

CODE  
DPEX6AC

CAPACITY  
6KG

FIRE RATING  
34A 233B C

EXTINGUISHER MEDIUM  
ABC 40

WORKING PRESSURE  
14 BAR

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN



 <b>Water</b>	 <b>CO2</b>
 DO NOT use on electrical fires	 DO NOT use on flammable liquids
 DO NOT use on flammable gases	 DO NOT use on reactive metals
 DO NOT use on hot oil fires	 DO NOT use on oxidizing agents

**WATER**

**FIRE EXTINGUISHER**  
6 Litre WATER 13A

For use on wood, paper, fabric and other Class A fires.

- Use upright.
- Point nozzle at base of fire.
- Pull handle and aim at base of fire.
- Scan to cover.

**CAUTION**

Check for the manufacturer's instructions and warnings. Use weight and pressure to hold nozzle steady.

**CONTEMPO**

**CO2**

**FIRE EXTINGUISHER**  
2.5 Litre CARBON DIOXIDE 34

For use on electrical fires, flammable liquids, flammable gases, reactive metals, oxidizing agents and hot oil fires.

- Use upright.
- Point nozzle at base of fire.
- Scan to cover.

**CAUTION**

Check for the manufacturer's instructions and warnings. Use weight and pressure to hold nozzle steady.

**CONTEMPO**



# Contempo Stainless Steel

With a superb highly polished finish, luxury stainless steel extinguishers are perfect for areas where appearance is important.

Stainless steel is one of the most corrosion-resistant metals known, as well as being extremely strong. That means these units are among the toughest available and are proven to last – even in the harshest of environments. The Contempo range of Stainless Steel fire extinguishers benefits from the following:

## Features

- Manufactured to BS EN3
- Full range of spare parts available
- Corrosion-resistant finish
- Five-year warranty\*
- Super strong base skirt for protection
- Polyethylene internal lining (on water and foam units)
- We also have 9ltrs available in the range



**2kg CO2  
Stainless Steel**

CODE  
COEX2P

CAPACITY  
2KG

FIRE RATING  
34B

EXTINGUISHER MEDIUM  
CO2

WORKING PRESSURE  
56 BAR @ 20°C

TEMPERATURE RANGE  
-20+60°C

CYLINDER MATERIAL  
ALLOY STEEL

**6ltr AFF Foam  
Stainless Steel**

CODE  
FSEX6SS

CAPACITY  
6 LITRES

FIRE RATING  
13A 144B

EXTINGUISHER MEDIUM  
AFF FOAM

WORKING PRESSURE  
14 BAR

TEMPERATURE RANGE  
+5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN

**6ltr MultiCHEM  
Stainless Steel**

CODE  
FSEX6MCSS

CAPACITY  
6 LITRES

FIRE RATING  
34A 233B 75F

EXTINGUISHER MEDIUM  
FOAM

WORKING PRESSURE  
12 BAR

TEMPERATURE RANGE  
-5+60°C

CYLINDER MATERIAL  
ALLOY STEEL

PRESSURE GAS  
NITROGEN

**6ltr Water  
Stainless Steel**

CODE  
WSEX6SS

CAPACITY  
6 LITRES

FIRE RATING  
13A

EXTINGUISHER MEDIUM  
WATER

WORKING PRESSURE  
14 BAR

TEMPERATURE RANGE  
+5+60°C

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN

**6kg Powder  
Stainless Steel**

CODE  
DPEX6SS

CAPACITY  
6KG

FIRE RATING  
34A 233B C

EXTINGUISHER MEDIUM  
ABC 40

WORKING PRESSURE  
14 BAR

CYLINDER MATERIAL  
STEEL

PRESSURING GAS  
NITROGEN





GOOD  
VIBES  
ONLY





# Trolleys and Covers

Fire extinguisher trolleys and covers help to protect vital fire fighting equipment from corrosion, accidental damage and misuse.



**Double Trolley**

CODE  
CS23

WEIGHT  
16KG

DIMENSIONS (WHD)  
1200 X 720 X 400MM

FIRE EXTINGUISHERS  
2

ROBUST POWDER COATED  
STEEL FRAME

NYLON WHEELS

SPACE FOR FIRE BUCKET

SPACE FOR ALARM BELL /  
SITE ALARM

CAN BE ADAPTED  
TO HOLD CO2 FIRE  
EXTINGUISHERS



**Compact Double Trolley**

CODE  
CS23A

WEIGHT  
14KG

DIMENSIONS (WHD)  
1200 X 470 X 400MM

FIRE EXTINGUISHERS  
2

ROBUST POWDER COATED  
STEEL FRAME

NYLON WHEELS

SPACE FOR FIRE BUCKET

SPACE FOR ALARM BELL /  
SITE ALARM

COMPACT, SPACE SAVING  
DESIGN



**Backboard Double Trolley**

CODE  
CS23-DF

WEIGHT  
16KG

DIMENSIONS (WHD)  
1200 X 720 X 400MM

FIRE EXTINGUISHERS  
2

ROBUST POWDER COATED  
STEEL FRAME

NYLON WHEELS

SPACE FOR FIRE BUCKET

SPACE FOR ALARM BELL /  
SITE ALARM

A LARGE STEEL  
BACKBOARD FOR  
MOUNTING ALARM  
EQUIPMENT AND SIGNAGE



**Mobile Fire Point Stand**

CODE  
CS26A

WEIGHT  
20KG

DIMENSIONS (WHD)  
1800 X 890 X 480MM

FIRE EXTINGUISHERS  
4

ROBUST POWDER COATED  
STEEL FRAME

NYLON WHEELS

SPACE FOR FIRE BUCKET

SPACE FOR ALARM BELL /  
SITE ALARM

A LARGE STEEL  
BACKBOARD FOR  
MOUNTING ALARM  
EQUIPMENT AND SIGNAGE

ALSO AVAILABLE IN  
YELLOW AND GREEN



**PVC Extinguisher Cover (Medium)**

CODE  
CS22

FITS UP TO 6KG / 6LTR  
FIRE EXTINGUISHERS

QUALITY PVC MATERIAL

CLEAR VIEWING WINDOW

VELCRO STRAPS TO  
ALLOW FOR EASE OF  
FITTING AND SECURING



**PVC Extinguisher Cover (Large)**

CODE  
CS21

FITS UP TO 9KG / 9LTR  
FIRE EXTINGUISHERS

QUALITY PVC MATERIAL

CLEAR VIEWING WINDOW

VELCRO STRAPS TO  
ALLOW FOR EASE OF  
FITTING AND SECURING





Fire assembly p

FIRE ALARM



COMMANDER

**Water**

FIRE EXTINGUISHER  
8 LITRE WATER  
13 A

- Use upright  
Pull out safety pin
- Free hose  
Aim nozzle  
at base of fire
- Squeeze handles



COMMANDER EDGE

**Powder**

FIRE EXTINGUISHER  
Dry ABC powder  
5kg 33bar C

- Use upright  
Pull out safety pin
- Free hose  
Aim nozzle  
at base of fire
- Squeeze handles



COMMANDER EDGE



# Stands

Fire extinguisher stands are a versatile solution for display where wall-mounting might not be appropriate.



**Single Tubular Stand**

CODE CS30
WEIGHT 1.75KG
DIMENSIONS 840 X 390 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

\*OPTIONAL



**Double Tubular Stand**

CODE CS31
WEIGHT 2.5KG
DIMENSIONS 840 X 500 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

\*OPTIONAL



**Single Tubular Stand**

CODE CS32
WEIGHT 1.75KG
DIMENSIONS 840 X 390 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
AVAILABLE IN RED, STAINLESS STEEL, ANTIQUE COPPER AND POLISHED GOLD
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

\*OPTIONAL



**Double Tubular Stand**

CODE CS33
WEIGHT 2.5KG
DIMENSIONS 840 X 500 X 300MM
DESIGNATED SPACE FOR ID SIGNS, NO CLIPS REQUIRED
NO DRILLING OR FIXING REQUIRED
EASILY RELOCATE AS NEEDED
BASE GRIPS FOR FLOOR PROTECTION
STRONG AND LIGHTWEIGHT, ALLOWING FOR EASY TRANSPORTATION
AVAILABLE IN RED, STAINLESS STEEL, ANTIQUE COPPER AND POLISHED GOLD
SUITABLE FOR - EXTINGUISHERS SIZES 2KG-9KG WITH THE EXCEPTION OF A 5KG CO2*

\*OPTIONAL



**Commander Single Extinguisher Stand**

CODE CS50
WEIGHT 1.2KG
DIMENSIONS 280 X 750 X 275MM
SUITABLE FOR MAX 200MM
RELIABLE AND ROBUST PP PLASTIC MATERIAL
COMBINATION OF BOTH A MATT AND GLOSS FINISH
DEDICATED AREA FOR SIGNAGE APPLICATION
GRIPPED BASE TO PROTECT FLOOR SURFACE
EASILY COMBINE TO MAKE A TRIPLE PLUS STAND
IMMEDIATE ACCESS TO THE FIRE EXTINGUISHER
ENVIRONMENTALLY FRIENDLY MATERIALS



**Commander Double Extinguisher Stand**

CODE CS51
WEIGHT 2.3KG
DIMENSIONS 548 X 750 X 288.5MM
SUITABLE FOR MAX 200MM
RELIABLE AND ROBUST PP PLASTIC MATERIAL
COMBINATION OF BOTH A MATT AND GLOSS FINISH
DEDICATED AREA FOR SIGNAGE APPLICATION
GRIPPED BASE TO PROTECT FLOOR SURFACE
EASILY COMBINE TO MAKE A TRIPLE PLUS STAND
IMMEDIATE ACCESS TO THE FIRE EXTINGUISHER
ENVIRONMENTALLY FRIENDLY MATERIALS



**Wave Wall Extinguisher Stand**

CODE WAVE/RED
WEIGHT 1.90KG
DIMENSIONS 386 X 234 X 400MM
SUITABLE FOR MAX DIAMETER 135-200MM
SOLID STRUCTURE FIVE FIXING POINTS
AVAILABLE IN RED AND WHITE





# Cabinets

Safely store fire extinguishers in a cabinet that protects against accidental damage, misuse and all-weather conditions.



**Single Commander Cabinet**

CODE  
CS01DA9

CAPACITY  
9KG/9LTR/2KG CO2

EXTERNAL DIMS (WHD)  
335 X 715 X 240MM

INTERNAL DIMS (WHD)  
264 X 652 X 204MM

FULLY WEATHER SEALED

RESISTANT TO CHEMICALS

BRILLIANT SHOCK RESISTANCE

INNOVATIVE INTERNAL CLAMP SYSTEM

MANUFACTURED FROM ABS

**Single Cabinet Extended**

CODE  
CS02DA

CAPACITY  
9KG/9LTR/5KG CO2

EXTERNAL DIMS (WHD)  
335 X 865 X 240MM

INTERNAL DIMS (WHD)  
264 X 816 X 204MM

FULLY WEATHER SEALED

RESISTANT TO CHEMICALS

BRILLIANT SHOCK RESISTANCE

INNOVATIVE INTERNAL CLAMP SYSTEM

MANUFACTURED FROM ABS

**Double Cabinet**

CODE  
CS03 DA

CAPACITY  
2 X 9KG/9LTR/2KG CO2

EXTERNAL DIMS (WHD)  
616 X 735 X 270MM

INTERNAL DIMS (WHD)  
530 X 700 X 229MM

FULLY WEATHER SEALED

RESISTANT TO CHEMICALS

BRILLIANT SHOCK RESISTANCE

INNOVATIVE INTERNAL CLAMP SYSTEM

MANUFACTURED FROM ABS

LOCKABLE

ALSO AVAILABLE IN YELLOW AND GREEN

**Commander Double Lockable Cabinet**

CODE  
CS03A DA

CAPACITY  
2 X 9KG/9LTR/2KG CO2

EXTERNAL DIMS (WHD)  
616 X 735 X 270MM

INTERNAL DIMS (WHD)  
530 X 700 X 229MM

FULLY WEATHER SEALED

RESISTANT TO CHEMICALS

BRILLIANT SHOCK RESISTANCE

INNOVATIVE INTERNAL CLAMP SYSTEM

MANUFACTURED FROM ABS

LOCKABLE

**Vehicle Extinguisher Cabinet 6kg / 9kg**

CODE  
CS04 DA / CS05 DA

WEIGHT  
2.1KG

EXTERNAL DIMS (WHD)  
265X284X595MM

INTERNAL DIMS (WHD)  
224X224X561MM

EXTINGUISHER DIAMETER  
140/160MM

NYLON TENSION SPRING (Ø 140/160 MM)

EXTRA TENSION SPRINGS\* < Ø 140 MM(Ø 140/160 MM)

NYLON HANDLE SEALABLE OR LOCKABLE

REINFORCED AND NON DEFORMABLE STRUCTURE

INTERNAL TPE SEAL AGAINST WATER AND DUST

BRACKETS CAN BE MOUNTED ON ANY SIDE

\*OPTIONAL

**Commander Safety Box**

CODE  
CS60

CAPACITY  
4 X 6LTR/6KG

EXTERNAL DIMS (WHD)  
655 X 520 X 570MM

INTERNAL DIMS (WHD)  
536 X 420 X 537MM

INTERNAL TPE SEAL AGAINST DUST AND WATER INGRESS

HIGH RESISTANCE TO: WATER AND DUST INGRESS, UV RAYS, HIGH AND LOW TEMPERATURES

SMOOTH, FLAT ROOF FOR SIGN APPLICATION

ERGONOMIC SIDE HANDLES FOR EASY CARRYING

ALSO AVAILABLE WITH COMMANDER CONTACT ALARM – SEE PAGE 42

# Fire Extinguisher Signs

Fire extinguisher ID signs clearly identify the location of fire extinguishers within a building and inform users of their contents. Signs are available on white rigid plastic and can be photoluminescent to ensure visibility in all conditions.



## Water ID Sign

CODE  
101P / 111P

SIZES  
75 X 200MM  
150 X 100MM

## Foam ID Sign

CODE  
102P / 112P

SIZES  
75 X 200MM  
150 X 100MM

## CO2 ID Sign

CODE  
103P / 113P

SIZES  
75 X 200MM  
150 X 100MM

## Powder ID Sign

CODE  
104P / 114P

SIZES  
75 X 200MM  
150 X 100MM

## Wet Chemical ID Sign

CODE  
105P / 115P

SIZES  
75 X 200MM  
150 X 100MM

## Fire Blanket ID Sign

CODE  
106P / 116P

SIZES  
75 X 200MM  
150 X 100MM

## MultiCHEM ID Sign

CODE  
107P / 117P

SIZES  
76 X 200MM  
150 X 100MM

# Emergency Escape Signs

Clearly demonstrate where the nearest emergency exit is situated to direct people safely off the premises.



**Fire Exit  
(Right) Sign**

CODE  
201P / 211S  
SIZES  
300 X 100MM  
450 X 150MM



**Fire Exit  
(Up) Sign**

CODE  
202P / 212R  
SIZES  
300 X 100MM  
450 X 150MM



**Fire Exit  
(Down) Sign**

CODE  
203P / 213S  
SIZES  
300 X 100MM  
450 X 150MM



**Fire Exit  
(Left) Sign**

CODE  
204P / 214S  
SIZES  
300 X 100MM  
450 X 150MM



**Fire Exit  
(Up Left) Sign**

CODE  
207P / 217P  
SIZES  
300 X 100MM  
450 X 150MM



**Fire Exit  
(Down Right) Sign**

CODE  
205P / 215S  
SIZES  
300 X 100MM  
450 X 150MM



**Fire Exit  
(Up Right) Sign**

CODE  
206P / 216S  
SIZES  
300 X 100MM  
450 X 150MM



**Fire Exit  
(Down Left) Sign**

CODE  
208P / 218P  
SIZES  
300 X 100MM  
450 X 150MM



**Final Fire  
Exit Sign**

CODE  
301P  
SIZE  
300 X 150MM



**Final Fire Exit  
(Man Left) Sign**

CODE  
302R  
SIZE  
300 X 150MM



**Final  
Exit Sign**

CODE  
303R  
SIZE  
300 X 150MM



**Final Exit  
(Man Left) Sign**

CODE  
SIZE  
300 X 150MM



**Push Bar To  
Open Sign**

CODE  
306P / 307R / 315S  
SIZES  
300 X 100MM  
450 X 150MM  
300 X 150MM  
600 X 75MM



**Push Pad To  
Open Sign**

CODE  
308R  
SIZE  
300 X 100MM



**Fire Assembly  
Point Sign**

CODE  
702R 712R  
SIZES  
400 X 300MM  
600 X 400MM



**Fire Exit  
Keep Clear Sign**

CODE  
309R / 310P  
SIZES  
450 X 150MM  
200 X 200MM



# Fire Action, Equipment and Door Signs

Ensure all users of the building are aware of the location of vital fire-fighting equipment and fire doors and understand exactly what action to take.



**Fire Action  
Standard Sign**

CODE  
401P  
SIZE  
150 X 200MM



**Fire Action  
Picto Sign**

CODE  
402P  
SIZE  
150 X 200MM



**Fire Alarm Call  
Point Sign**

CODE  
501P  
SIZE  
150 X 200MM



**Fire  
Extinguisher Sign**

CODE  
502P  
SIZE  
150 X 200MM



**Fire Hose  
Reel Sign**

CODE  
503P  
SIZE  
150 X 200MM



**Fire  
Point Sign**

CODE  
504P  
SIZE  
150 X 200MM



**Call Point  
Picto Sign**

CODE  
505P  
SIZE  
100 X 100MM



**Fire Extinguisher  
Picto Sign**

CODE  
506P  
SIZE  
100 X 100MM



**Fire Alarm Call  
Point Sign**

CODE  
511R  
SIZE  
200 X 300MM



**Fire  
Extinguisher Sign**

CODE  
512R  
SIZE  
200 X 300MM



**Fire Hose  
Reel Sign**

CODE  
503P  
SIZE  
200 X 300MM



**Fire  
Point Sign**

CODE  
514S  
SIZE  
200 X 300MM



**Automatic Fire  
Door Sign**

CODE  
901R  
SIZE  
100 X 100MM



**Fire Door Keep  
Shut Sign**

CODE  
902R  
SIZE  
100 X 100MM



**Fire Door Keep  
Locked Shut Sign**

CODE  
903R  
SIZE  
100 X 100MM



**Fire Door Keep  
Closed Sign**

CODE  
904R  
SIZE  
100 X 100MM

# Alarms

Manually raise the alarm in times of emergency to ensure all users of the building are made aware they should vacate.



**Commander Alert Site Alarm**

CODE  
AE25

WEIGHT  
670G

DIMENSIONS (WHD)  
170 X 250 X 80MM\*

ALARM SOUND LEVEL  
115DB

12 LED SUPER BRIGHT STROBE

ABS CASE RESISTS SHOCKS AND DROPS

SIMPLE FITTING AND OPERATION

RADIO LINK MODULE AVAILABLE

IP65 RATED

\*(INCLUDING ACTIVATION BUTTON AND STROBE/SIREN)



**Commander Alert Site Alarm Wireless**

CODE  
AE25/W

WEIGHT  
670G

DIMENSIONS (WHD)  
170 X 250 X 80MM\*

ALARM SOUND LEVEL  
115DB

12 LED SUPER BRIGHT STROBE

ABS CASE RESISTS SHOCKS AND DROPS

SIMPLE FITTING AND OPERATION

RADIO LINK MODULE AVAILABLE

IP65 RATED

\*(INCLUDING ACTIVATION BUTTON AND STROBE/SIREN)



**Smoke Alarm**

CODE  
AE20

WEIGHT  
130G

DIMENSIONS (DH)  
110 X 370MM

ALARM SOUND LEVEL  
85DB

TECHNOLOGY  
IONISATION SMOKE SENSOR

BATTERY TYPE  
9V ALKALINE

WARRANTY  
5 YEARS

CEILING INSTALLATION



**Commander Contact Alarm**

CODE  
AE15

WEIGHT  
100G

DIMENSIONS (ØD)  
87 X 87 X 43MM

ALARM SOUND LEVEL  
85DB-110DB

BATTERY OPERATION  
6F22 9V BATTERY

SIMPLE FITTING AND OPERATION

SUITABLE FOR USE ON THE CS60 AND ALL CABINETS OF ALARM FUNCTION



**Carbon Monoxide Alarm**

CODE  
AE23

WEIGHT  
115G

DIMENSIONS (ØD)  
140 X 35.5MM

ALARM SOUND LEVEL  
85DB

BSI KITEMARKED  
EN50291

BATTERY OPERATION  
3 X AA ALKALINE BATTERIES SUPPLIED AS STANDARD

WARRANTY  
5 YEARS

TEST/RESET BUTTON TO ALLOW REGULAR TESTING OF ALARM FUNCTION



**Rotary Alarm Bell**

CODE  
AE01

WEIGHT  
1.57KG

DIMENSIONS (ØD)  
274MM X 89.4MM

ALARWM SOUND LEVEL  
85DB

SUITABLE FOR USE INDOORS AND OUTDOORS

HAND-OPERATED FIRE ALARM BELL

ALUMINIUM ALLOY



**Air Horn Alarm**

CODE  
AE02

ACOUSTIC RANGE  
APPROX. 1500M

IDEAL FOR PROVIDING TEMPORARY COVER

IDEAL FOR CONSTRUCTION SITE APPLICATIONS



# Intumescent Products

Intumescent sealants, strips and other items help slow down the spreading of fire to provide more time for evacuation of the building.



**Intumescent Strip**

Intumescent strip is a vital ancillary product for any door. Available as either brush pile or rubber fins, the strip works to seal around vulnerable edges of a fire door. We stock intumescent strip in a range of sizes.



**Door Closers**

Fire doors must be kept shut at all times to remain a crucial barrier to prevent the spread of smoke and fire. Door closers ensure a fire door is automatically closed after it's been opened. They also help to remove some the weight of this heavy door, meaning they offer a practical solution for certain settings.



**Drop Seals**

Fire doors require automatic drop-down seals, which provide an effective barrier against climate, noise, light, fire, smoke and insects. Once the door is closed, a plunger-like system ensures the gap between the door and flooring is closed. Choose from a range of seals suitable for glass and timber doors.



**Mastic and Foam**

These sealants help prevent the spread of smoke and fire. In the event of a fire, fire-resistant expanding foam fills gaps around fire doors, joints and holes in fire-rated structures, while intumescent sealant swells to create a seal.



**Grilles**

For easy installation in walls and fire doors, intumescent grilles allow ventilation where required and form a barrier to prevent the spread of smoke and fire. Grilles are used to provide fire dampers in ductwork.



**Collars and Wraps**

Pipes that penetrate fire compartment walls must be fitted with a fire prevention solution – either intumescent pipe collars or wraps. These items are fixed where the pipes intersect the wall or floor and when exposed to heat, expand to plug any gaps.

# Ancillary Products

Provide support to vital fire safety equipment with our extensive selection of ancillary products, which are fully compliant with British Standards.



**Engineer's Tool Kit (Standard)**

CODE  
ST49

- 1KG SPRING BALANCE
- 20KG SPRING BALANCE
- TG HEADCAP SPANNER
- BRITANNIA 'C' SPANNER
- ALLEN KEYS
- ADJUSTABLE SPANNER
- GLORIA HEADCAP 'T' BAR
- FIREPOWER HEADCAP 'T' BAR
- GAUGE TESTER MIJA
- STANDARD ENGINEER'S TORCH
- RUBBER MALLET
- NYLON VALVE BRUSH
- BRASS VALVE BRUSH
- 200ML WD40
- 'O' RING REMOVAL TOOL
- PETROLEUM JELLY 200G
- POWDER BLOW OUT BAG



**Engineer's Tool Kit (Advanced)**

CODE  
ST50

- INCLUDES STANDARD ENGINEER'S TOOL KIT PLUS:
- DIGITAL SCALE
- MAGLITE® TORCH
- LED INSPECTION LAMP
- GAUGE TESTER EBUR WIKA
- LEAK DETECTOR SPRAY
- 'V' CLAMP
- PLASTIC FUNNEL



**Year Gauge Indicator Dots**

CODE  
ST03

- SHOWS THE GAUGE HAS BEEN TESTED
- AVAILABLE IN VARIOUS COLOURS AND CLEAR
- IN ACCORDANCE WITH BS5306



**Pull Tite Seals**

CODE  
PS09

- SELF LOCKING SEAL NO TOOLS REQUIRED
- PROTECTS AGAINST TAMPERING AND ACCIDENTAL DISCHARGE
- 10 SEALS PER MAT



**Chubb Type Pin and Discs**

CODE  
PS04

- PIN DIAMETER 7MM
- COLOURS AVAILABLE GREEN, BLUE, YELLOW, RED, WHITE, ORANGE, BLACK



**Commander Fire Blankets**

CODE  
FB01 / FB02 / FB03

- SIZES 1 X 1M, 1.2 X 1.2M, 1.8 X 1.2M
- BLANKET MATERIAL SILICONE COATED FIBERGLASS FABRIC
- OUTER CASE MATERIAL PP CASE



**Fire Safety Log Book**

CODE  
A4LOG / A5LOG

- SIZES A4, A5
- COMPLETED FOLLOWING INSPECTIONS, TESTING AND ANY MAINTENANCE OF FIRE SAFETY EQUIPMENT



# Ancillary Products



**Service Labels**

CODE  
ST04

DIMENSIONS  
70 X 100MM

RECORD INSPECTION  
DETAILS

FULL COLOUR PRINT

SELF-ADHESIVE

BRANDING AVAILABLE



**O-rings**

CODE  
PP144

PIN DIAMETER  
7MM

COLOURS AVAILABLE  
GREEN  
BLUE  
YELLOW  
RED  
WHITE  
ORANGE  
BLACK



**Digital Hand-Held Scales**

CODE  
ST08

WEIGHT  
25KG X 20G

COLOURS AVAILABLE  
COMPLETE WITH TARE AND  
READING HOLD FACILITY

COLOURS AVAILABLE  
BATTERY OPERATED



**20ltr Foam Drum Refill**

CODE  
RP21

A FULL RANGE OF FOAM  
FOR ALL APPLICATIONS



**20ltr Wet Chem Refill**

CODE  
CH01

SUITABLE FOR 2KG CO2  
FIRE EXTINGUISHERS



**CO2 Horns  
2KG / 5KG**

CODE  
CH05

SUITABLE FOR 2KG / 5KG  
CO2 FIRE EXTINGUISHERS

WITH A DIRECT SWIVEL  
ACTION AND IS EASY  
TO FIT ON TO FIRE  
EXTINGUISHERS



**Plastic Fire Bucket & Lid**

CODE  
FBK01

CAPACITY  
10LTR



FIRE & SECURITY

MARLOWE *Critical Services*

Fire Protection

Security Systems

National Coverage

Connected Services

Unit 3 Roebuck Place  
110 Roebuck Road  
Chessington  
Surrey  
KT9 1EU

**t:** 020 8974 1177

**e:** [connect@fafs.biz](mailto:connect@fafs.biz)

**w:** [www.fafs.biz](http://www.fafs.biz)